



F24 SLATE HOOK 80-120



TOOL FEATURES

- Safe and efficient tool for installing roof hooks without breaking roof slate
- Lightweight and easy to use
- Power to drive through wood knots

SLATE ROOFING HOOK

Collated Slate Roofing Hooks are an innovation of BECK. The collated roofing hooks are pneumatically driven with the new Slate Hook Nailer and represent the fastest, safest and most efficient slate shingle installation method to date.



CONTACT & SERVICE

Our sales team
is available at:

T +43 7724 2111-671
sales@beck-fastening.com
www.beck-fastening.com

DESCRIPTION

- Precise fastener length for visually consistent slate roofing
- Slate tile insertion hooks with diamond point to better repel water and dirt
- Residue-free collation prevents plastic debris flying around
- High strip integrity is still given in wet conditions
- Comply with European standards (NF32-201-1) including all technical specifications for roofing with slate
- Damaged shingles can be replaced easily

F24 SLATE HOOK 80-120

APPLICATIONS

- Slate roofing

Especially developed for slate roof installation which does not harm the slate tiles. One handed installation makes working on steep pitch roof easier freeing the other hand for balance.

HANDLING

1. Load fastener from the side into the magazine
2. Connect air supply
3. Avoid a dry and dirty tool by cleaning and lubricating regularly

TOOL CHARACTERISTICS

Height	Width
201 mm	205 mm
7.91 inch	8.10 inch
Length	Weight
212 mm	3,63 kg
8.35 inch	1.65 lbs

Pressure

5.6 - 8.4 bar | 81 - 120 psi

Air consumption per shot

0.524 L. | 0.019 SCF
Performance at 90 psi | 6.2 bar
(0.62 MPa)

FASTENER DATA

	Slate Roofing Hook
A) Diameter	2.70 mm 0.106"
L) Length	80 - 125 mm 3 1/8 - 4 7/8"
O) Standard Opening	4.8 mm 0.188"
Capacity	50

NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$: 92.20 dB (A) - $K_{WA,1s}$, 2.5

$L_{pA,1s}$: 89.40 dB (A) - $K_{pA,1s}$, 2.5

VIBRATION VALUE

(UNI ISO/TS 8662-11)

1.47 m/s²

ACTUATION & LOADING

Actuation System:

Contact actuation

Loading: Side Loading

VARIATIONS

Upon request, also available with 9 mm opening

FURTHER INFORMATION

FINISH:

- unpainted
- black painted

MATERIAL:

Stainless steel:

- SS430 (unpainted)
- SS304 | A2 (black painted)
- SS316 | A4 (black painted)

