

- Engineered for the power and durability required for use with light gauge steel
- Accepts T-Nail style hardened trim pins
- Power to fasten to 14 ga steel at the speed of nailing to wood
- Operates using typical jobsite air compressor at 120 psi maximum
- Capable of driving pins 11/2" to 3" long
- Systems approach with tools and fasteners provides single source responsibility
- Comes standard with plastic carrying case
- No-Mar tip
- · Depth of drive adjustment



CONTACT & SERVICE

Our sales team is available at:

P +1 800 248 2376

E etf@beck-fastening.com W www.beck-fastening.com

PIN TYPE

AST-100 TRIMFAST® HEAVY DUTY TRIM PINS



Trimfast® Heavy Duty Model 210TA

TOOL CHARACTERISTICS

Height	Width	Length	Weight
11 1/2 inch	3 1/2 inch	12 inch	6.56 lbs
292 mm	89 mm	305 mm	3 kg

Pressure 85 - 120 psi | 6 - 8 bar

Lubricant Non-detergent pneumatic tool lubricant

Recommended steel thickness

20 ga - 14 ga



Model 210TA

FASTENER DATA

Pin Type	AST-100-0150G	AST-100-0200G	AST-100-0250G	AST-100-0300G	
Wire	0.086" 2.20 mm				
Shank	Smooth				
Head	1/4" 6 mm				
Length	11/2" 39 mm	2" 50 mm	2 1/2" 63 mm	3" 75 mm	
Coating	Electro Galvanized				
Magazine Capacity	80 pins				

ACTUATION & LOADING

Actuation System: Sequential fire Loading: Magazine with latch

APPLICATIONS

- James Hardie® XLD fiber cement trim to light gauge steel framing
- Miratec® treated exterior composite trim to light gauge steel framing
- Wood furring and exterior trim to light gauge steel framing
- Wood or metal furring to CMU