



**F44AC CN15W-
PS65 BULL'S EYE**



**TOOL
FEATURES**

- Special Bull's eye safety designed for insulation attachment
- Suitable for both wire welded and plastic sheet coil nails & SCRAIL®
- Switchable trigger for single shot and bump fire

SCRAIL®

- Twice as fast as collated screws
- Eight times faster than bulk screws
- Can be used for almost all screw applications
- Easily installed, quickly removed
- Dramatically increased holding power versus nails



CONTACT & SERVICE

Our sales team
is available at:

P +1 800 239 8665
sales@beck-america.com
www.beck-america.com

DESCRIPTION

FASCO Bull's Eye Washer System, when used with our SCRAIL® fasteners, this system provides a fast and efficient method for attaching metal or plastic washers for a wide variety of applications using our FASCO SCRAILers.

- 1 3/4" dia. Plasti-Grip® ci prong washer w/UV inhibitor
- Pre-spotting prongs reduce labor cost
- Galvanized washers 1 1/4" diameter
- 1 1/4" dia. Grip-Plate® Lath & Plaster washer

F44AC CN15W-PS65 BULL'S EYE

APPLICATIONS

- Lath / stucco
- Building wrap
- Rigid / continuous (CI) insulation
- Exterior foundation insulation
- Wet rooms
- Other construction applications

HANDLING

1. Adjust magazine plate to nail length
2. Position first nail in nose channel and align top nails with upper edge loading channel
3. Connect air supply
4. Avoid a dry or dirty tool by lubricating respectively cleaning regularly

TOOL CHARACTERISTICS

Height	Width
322 mm	130 mm
12.67 inch	5.12 inch
Length	Weight
275 mm	2,40 kg
10.82 inch	5.29 lbs

Pressure

5 - 8 bar | 70 - 120 psi

Air consumption per shot

1.20 L. | 0.042 SCF

Performance at 90 psi | 6.2 bar
(0.62 MPa)

NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$: 92.02 dB (A) - $K_{WA,1s}$, 2.5

$L_{pA,1s}$: 81.50 dB (A) - $K_{pA,1s}$, 2.5

VIBRATION VALUE

(UNI ISO/TS 8662-11)

3.47 m/s²

ACTUATION & LOADING

Actuation System: Single Shot
& Contact Actuation

Loading: Coil

VARIATIONS

F44AC CN15W-PS65

F44AC CN15W-PS65 SCR

FASTENER DATA

NAILS

	Wire	Plastic
Diameter	2.30 - 2.80 mm 0.091 - 0.110"	
Shank	smooth ring screw knurled	
Pitch	7 - 8 mm 0.275 - 0.314"	7.50 mm 0.295"
Head	5 - 7 mm 0.197 - 0.275"	
Magazine Capacity	250 - 400	200
Nail Type	15° Wire Coil Nails 15° Plastic Sheet Coil Nails (CN-AG)	

FASTENER DATA

SCRAIL®

Diameter	2.50 - 3.50 mm 0.098 - 0.138"
Head	Phillips® Pozi Torx®/Star Versa
Length	30 - 57 mm 1.181 - 2 ¼"
Magazine Capacity	200 - 300
SCRAIL® Type	15° Wire Coil SCRAIL® 15° Plastic Sheet Coil SCRAIL® (CN-AG)

Changes and errors excepted. All rights reserved.

FASCO® and SCRAIL® are registered trademarks of the RAIMUND BECK KG.

Torx®, Phillips® and Pozi (PoziDrive®) are all trademarks of their respective owners.

VERSION
04/2021 US